



4051 Rope-operated extension ladder, two-section

- › Inner width of the ladder 300 mm (upper section).
- › Rolled profile rungs.
- › Solid guide fittings made of steel.
- › Maximum grip rope (Ø 10 mm), for safe height adjustment.
- › With wall rollers for a comfortable extending of the ladder.
- › **NEW:** All sizes with cross-beam.



Number of rungs		2×14	2×16	2×18	2×20
Stile top/bottom	approx. mm	83/83	89/89	89/89	89/89
Number of rungs at max. extension		25	29	32	36
Length retracted	approx. m	4.11	4.67	5.23	5.79
Length extended	approx. m	7.18	8.30	9.14	10.26
Standing height	approx. m	5.97	7.05	7.86	8.95
Working height	approx. m	7.47	8.55	9.36	10.45
Reach height	approx. m	7.97	9.05	9.86	10.95
Width extended top/bottom	approx. mm	355/1,200	355/1,200	355/1,200	355/1,200
Weight	approx. kg	18.8	23.5	26.5	30.4
EAN-Code		4019502339248	4019502339255	4019502339262	4019502339279
Order no.		405128	405132	405136	405140

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



P. 138
Cross-beam for ladder section for retrofitting




P. 136
Set of foot pikes for stiles



P. 140
Telescopic wall spacer for rung ladders



P. 140
Ladder holder set for gutters



P. 144
Ladder bracket set for roof racks