





## 6051 Rope-operated extension ladder, two-section

- › Inner width of the ladder 300 mm (upper section).
- › Rungs made of extruded profiles with deep ribbing, and therefore increased slip resistance.
- › Inside fittings ensure better guidance and high stability: The stile can be held on the outside when extending and retracting the ladder without the risk of crushing one's fingers.
- › Maximum grip rope (Ø 12 mm), for safe height adjustment.
- › With wall rollers for a comfortable extending of the ladder.
- › **NEW:** With extendible supports (space-saving design for transport).
- › Folding feet with large bearing surface and high stability.



Number of rungs		2×14	2×16	2×18	2×20	2×22
Stile top/bottom	approx. mm	89/89	89/89	89/89	100/100	100/100
Number of rungs at max. extension		25	29	32	36	40
Length retracted	approx. m	4.19	4.75	5.31	5.87	6.43
Length extended	approx. m	7.27	8.39	9.23	10.35	11.47
Standing height	approx. m	6.19	7.29	8.12	9.22	10.32
Working height	approx. m	7.69	8.79	9.62	10.72	11.82
Reach height	approx. m	8.19	9.29	10.12	11.22	12.32
Width extended top/bottom	approx. mm	355/1,400	355/1,400	355/1,400	355/1,400	355/1,400
Weight	approx. kg	25.1	27.4	31.2	36.8	41.6
EAN-Code		4019502338630	4019502338647	4019502338654	4019502338661	4019502338678
Order no.		605128	605132	605136	605140	605144

For an explanation of working/standing/reach height see on page 5.

### Recommended accessories:




Set of foot pikes for stiles



Telescopic wall spacer for rung ladders



Ladder holder set for gutters



Ladder bracket set for roof racks



Kit for telescopic stabiliser for leaning, extension and rope-operated ladders