



6875 Aluminium step complying with EN 14183

- › Comfortable working through large standing surface.
- › Two-part steps 232 mm deep, top step 355 mm.
- › Vertical step distance 240 mm.
- › Permissible load 150 kg (1.5 kN).
- › Shipped in single parts which are prepared for self-assembly.
- › Accessories available: set of wheels for easy mobility and retailing brackets.



| Number of steps | | 2 | 3 | 4 |
|-----------------------------------|------------|---------------|---------------|---------------|
| Stile | approx. mm | 40 | 40 | 40 |
| Standing height (height top step) | approx. m | 0.48 | 0.72 | 0.96 |
| Working height | approx. m | 1.98 | 2.22 | 2.46 |
| Reach height | approx. m | 2.48 | 2.72 | 2.96 |
| Step width top step | approx. mm | 585 | 571 | 556 |
| Step width lowest step | approx. mm | 600 | 600 | 600 |
| Overhang | approx. m | 0.68 | 0.95 | 1.21 |
| Weight | approx. kg | 7.1 | 9.7 | 11.4 |
| EAN-Code | | 4019502314641 | 4019502314665 | 4019502343351 |
| Order no. | | 687526 | 687536 | 687546 |

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



P. 143

Guardrail lateral

- › Order no. 0054896



P. 142

Fixed castor set

- › Order no. 0054448