




8012 Leaning step ladder

- › Ideal for industry and warehouses.
 - › Strengthened steps with 80 mm step depth. Front step edges flush with stile.
 - › Perforations for assembly of suspension hooks or supporting board present.
 - › Easily replaceable ladder shoes screwed onto stile and with large contact surface.
 - › Pre-assembly of support board or suspension hooks possible.
- Overall assembly costs per ladder (without support board/suspension hooks).



Number of steps		6	7	8	9	10	11
Stile	approx. mm	71	71	71	71	71	71
Length	approx. m	1.73	1.95	2.23	2.48	2.73	2.97
Standing height	approx. m	0.70	0.95	1.20	1.45	1.70	1.95
Working height	approx. m	2.20	2.45	2.70	2.95	3.20	3.45
Reach height	approx. m	2.70	2.95	3.20	3.45	3.70	3.95
Vertical height up to leaning point	approx. m	1.60	1.80	2.05	2.25	2.50	2.75
Vertical height to top step	approx. m	1.40	1.65	1.85	2.10	2.30	2.55
Width	approx. mm	405	405	405	405	405	405
Weight	approx. kg	4.0	4.6	5.2	5.8	6.4	7.0
EAN-Code		4019502315938	4019502315945	4019502315952	4019502315969	4019502315976	4019502315983
Order no.		801206	801207	801208	801209	801210	801211

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



P. 138

Cross-beam for ladder section for retrofitting



P. 140

Support board set



P. 139

Suspension hook set