




8024 Step ladder, double-sided accessible

- › Extremely robust step ladder for industry and trade.
- › Strengthened steps with 80 mm step depth. Front step edges flush with stile.
- › Solid cast-aluminium joints (easily replaceable).
- › Spreader lock provided by high-strength, 30 mm wide nylon straps.
- › Stable stiffening braces on first step.
- › Easily replaceable ladder shoes screwed onto stile and with large contact surface.



Number of steps		2×2*	2×3	2×4	2×5	2×6	2×7	2×8	2×9	2×10	2×12
Stile	approx. mm	71	71	71	71	71	71	71	71	71	71
Length	approx. m	0.53	0.77	1.04	1.30	1.53	1.80	2.05	2.28	2.54	3.04
Standing height	approx. m	0.22	0.22	0.45	0.69	0.92	1.15	1.38	1.61	1.85	2.31
Working height	approx. m	1.72	1.72	1.95	2.19	2.42	2.65	2.88	3.11	3.35	3.81
Reach height	approx. m	2.22	2.22	2.45	2.69	2.92	3.15	3.38	3.61	3.85	4.31
Vertical height	approx. m	0.45	0.70	0.95	1.15	1.40	1.65	1.85	2.10	2.30	2.80
Width top/bottom	approx. mm	355/410	355/430	355/450	355/475	355/500	355/525	355/550	355/575	355/600	355/650
Base width	approx. m	0.60	0.80	0.98	1.15	1.30	1.50	1.70	1.95	2.15	2.50
Weight	approx. kg	3.2	4.6	5.6	6.8	8.2	9.4	10.5	12.2	13.8	16.5
EAN-Code		4019502316034	4019502316041	4019502316058	4019502316065	4019502316072	4019502324916	4019502316089	4019502340114	4019502316096	4019502316102
Order no.		802404	802406	802408	802410	802412	802414	802416	802418	802420	802424

* The size 2×2 cannot be used according to DIN EN 131 and may only be accessed on the bottom-most step. Therefore make sure that sufficient safety is provided (e. g. by holding to a fixed point).

For an explanation of working/standing/reach height see on page 5.

Recommended accessories:



4 spring-loaded castors+2 rigid safety bars at HYMER assembled

› Swivelling/fixed castors can be freely selected depending on version. (Please specify which version of spring-loaded castor attachment you require when

placing your order.)

It is recommended to fit spring-loaded castors depending on the sense of safety of the user but only up to size 2×8.



P. 141

Sets of spring-loaded castors and sets of rigid safety bars for self assembly

› Swivelling/fixed castors freely chooseable.

	Variant 1	Variant 2	Variant 3	Variant 4
Ladder section 1	2 swivelling castors (one of the castors features a locking brake)	2 swivelling castors (one of the castors features a locking brake)	2 fixed castors	2 fixed castors
Ladder section 2	2 fixed castors	2 swivelling castors (one of the castors features a locking brake)	2 fixed castors	2 swivelling castors (one of the castors features a locking brake)
Rigid safety bars	2 rigid safety bars	2 rigid safety bars	2 rigid safety bars	2 rigid safety bars

¹⁾Swivelling castor without locking brake; ²⁾Swivelling castor with locking brake; ³⁾Fixed castor

Spare part:

› Spare parts set hinges, order no. 0053864, see on page 151.